

THE GLENHAM FIRE DISTRICT STANDARD OPERATING PROCEDURE	SUBJECT NO. GFD-43-23
DEPARTMENT: Glenham Fire Department SUBJECT: Emergency Escape and Self-Rescue Rope System	
<u>CROSS-REFERENCE:</u> GFD-43-01 Organizational Statement & General Overview; GFD-43-04 Officer Responsibilities; GFD-43-05 Firefighter Classifications; GFD-43-06 Training Requirements; GFD-43-07 Issuing of Department Gear and Equipment; Monthly Rescue Rope Self-Inspection and Cleaning Log	

Original date of issue: 03/01/2018

Reviewed:	03/01/18	02/19	02/20				
Revised:	05/03/18						

PURPOSE

1. Establishes the Glenham Fire District procedure regarding the use of the Emergency Escape and Self-Rescue Rope System.
2. Defines the department and the qualified Interior Structural Firefighter in the use and training of the Emergency Escape and Self-Rescue Rope System.
3. Defines the department responsibility in the care use and inspection of the Emergency Escape and Self-Rescue Rope System and its components.

RESPONSIBILITIES

1. Chief Officers and/or their designee will enter the receipt of all Emergency Escape and Self Rescue Rope Systems into inventory.
2. Chief Officers and/or their designee have the joint responsibility to ensure all personnel are in compliance with this Procedure.
3. Chief Officers and/or their designee have the joint responsibility to ensure all training and documentation is in compliance with all applicable laws and regulations.

4. All Interior Structural Fire Fighters will wear their Emergency Escape and Self Rescue Rope System on all structural fire responses.
5. Emergency Escape and Self-Rescue Rope System will consist of the following components:
 - a. 1 Escape Harness
 - b. 1 50-foot Escape Rope
 - c. 1 Auto-locking Escape Device
 - d. 2 Screw lock carabineers
6. Incident Command will be responsible for ensuring that all Mutual Aid Interior firefighters, responding on Structural Fire related alarms, are equipped with appropriate Emergency Escape and Self Rescue Rope systems.

TRAINING

1. Training shall include hands-on use of the Emergency Escape and Self Rescue Rope System in a controlled environment. Firefighters should be informed of the limitations of the Emergency Escape and Self Rescue Rope System. Firefighters shall be instructed on how to perform the inspection of the Emergency Escape and Self Rescue Rope System.
2. A record of such instructional training including the name of the Firefighter being trained, the name of the competent person delivering the training and the date on which the training was provided should be maintained.
3. Complete Emergency Escape and Self Rescue Rope systems will be maintained for training purposes. Systems issued to individual members will not be used for training.
4. All Interior Structural Firefighters will be trained by a competent instructor on a semi-annual basis on the use (including inspection) of the Emergency Escape and Self-Rescue Rope System.
5. Each interior firefighter will demonstrate proficiency with the Emergency Escape and Self Rescue Rope System on a minimum yearly basis.

PROCEDURE

1. In the event an Interior Structural Firefighter becomes trapped by an uncontrolled emergency situation such as a rapid-fire advance, the use of the Emergency Escape and Self-Rescue Rope System provides the firefighter with the equipment to utilize a non-conventional opening, such as a window to escape the emergency

2. All Interior Structural Firefighters operating in a structure during interior firefighting activities will be equipped with an Emergency Escape and Self Rescue Rope System.
3. When a Firefighter determines it necessary to evacuate a structure at an elevation higher than the first floor of a structure using the Emergency Escape and Self Rescue Rope System, the firefighter will declare a May Day informing Incident Command of their situation. The Firefighter will escape the life-threatening situation by utilizing any convenient route of escape. In the case of a nonconventional route such as a window, the firefighter will deploy the Emergency Escape and Self Rescue Rope System issued and lower themselves in a controlled manner using the Emergency Escape and Self Rescue Rope System as it was designed and as trained in its use. The firefighter will lower themselves to:
 - a. The ground if enough escape rope is available
 - b. A lower floor safe from the danger to be pulled in by responding rescuers (Rapid Intervention Team)
 - c. To a safe position and stand-by to be rescued by portable ground ladder, or aerial device.
4. The Safety Harness is integrated into the pants of the turnout gear. External harnesses may be utilized in training evolution where necessary. The Emergency Escape and Self-Rescue Rope System will be stowed in the thigh pocket of the turnout gear pants. E. Incident Command or their designee will communicate the type of rescue that will be attempted to the Firefighter(s) on the incident scene.
5. Incident Command or their designee will declare an end to the May Day at the conclusion of the emergency escape evolution.

INSPECTION AND MAINTENANCE

1. All components of the Emergency Escape and Self Rescue Rope System will meet NFPA 1983 Standard on Life Safety Rope and Equipment for Emergency Services 2006 Edition.
2. When an Emergency Escape and Self Rescue Rope System becomes soiled, it will be cleaned following the manufacturers washing instructions.
3. Inspection of the Emergency Escape and Self Rescue Rope System will be completed monthly and after every use. The Emergency Escape and Self Rescue Rope System should be visually checked for cuts, chafed areas, glazed surfaces, discolorations and other damage such as dirt and mildew. The Escape Rope should be inspected by holding it firmly in one hand, pulling the rope between the thumb and index finger about 18 inches at a time, while feeling for broken fibers, soft or hard spots and

- variations in rope diameter. If any of the above is found, the Escape Rope shall be taken out of service immediately.
4. If the Emergency Escape and Self Rescue System has been subjected to a shock load, fall arrest or any other abuse, the rope shall be taken out of service, the rest of the system components shall be inspected for any damage or wear and retired if necessary.

RECORDKEEPING

1. In order to accurately track the history and use of the Emergency Escape and Self Rescue Rope System, recordkeeping must be maintained. A log will be kept for each Emergency Escape and Self Rescue Rope System issued to Interior Structural Firefighters. The log will contain the following information:
 - a. Description (Manufacturers name and model number) of the Emergency Escape and Self Rescue Rope System
 - b. Date of issuance
 - c. Dates of inspection
2. A checklist will be stored in each member's individual locker space at the fire station. It is the responsibility of the individual member to check their rope system on a monthly basis and sign off on the checklist that this has been completed. Any member not completing their monthly check will be suspended from interior firefighting until their equipment has been inspected.

Glenham Fire District

Monthly Rescue Rope Self-Inspection and Cleaning Log

Firefighter Name: _____

Date in Service: _____

Rope Diameter: _____ In. Rope Length: _____ Ft.

DATE		Inspected By:	Exposure	Incident Type	Comments
Month	Day				
Jan					
Feb					
Mar					
Apr					
May					
Jun					
Jul					
Aug					
Sep					
Oct					
Nov					
Dec					

Additional Comments:

REVISION HISTORY			
Rev	Description of Change	Author	Effective Date
1.0	Changed Subject No. from GFD-22-2018 to GFD-43-22. Changed from "Guideline" to "Procedure." Changed "should" to "shall" on P2, TRAINING, sentence's 1 and 3 and again under INSPECTION AND MAINTENANCE on P4, in item's 3 and 4.	David Dross, Deputy Chief	05/03/18